

Features:

- Integrated Cam Casing
- Easily Removable Impeller
- Easily Removable Cover Plate
- Versatile Drain Ports
- Innovated Shaft & Bearing
- Excellent Mechanical Seal
- Sealed Bearing Housing



	MODEL NUMBER						
	FG10	FG15	FG20	FG25	FG40	FG50	FG65
A	2-7/16	3-1/4	3-1/4	3-5/8	3-5/8	4-7/16	4-13/16
B	1-5/8	2-7/16	2-7/16	2-7/16	2-7/16	3-1/4	3-5/8
C	1-13/16	2	2-1/4	2-11/16	2-15/16	3-15/16	3-3/4
D	1-13/16	2	2-1/4	2-11/16	3-1/4	4	4-5/8
E	9/16	9/16	5/8	13/16	3-1/4	4	4-5/8
F	1-7/8	2-1/4	2-5/8	3-1/4	3-1/4	3-5/8	4-5/8
G	3-7/16	3-5/8	4-1/4	4-5/8	5-1/4	6	6-5/8
H	2-1/4	3-1/4	3-1/4	3-3/4	4-1/4	5-3/4	6-1/16
I	5-5/8	6-15/16	7-3/4	9	9-15/16	12-1/16	15-3/4
J	1-3/4	1-1/2	1-3/4	2-5/16	3	3-3/4	4-1/4
K	1-1/4	2	2	2-1/4	2-1/4	3-1/4	3-5/8
L	1-15/16	2-1/2	2-11/16	3-1/16	3-1/16	3-1/4	5-7/16
M	5/8	5/8	5/8	15/16	1-1/2	1-15/16	1-7/8
N	1/4	5/16	5/16	7/16	7/16	7/16	7/16
O	1/4	5/16	5/16	7/16	7/16	7/16	7/16
P	13/16	1	13/16	1-1/4	1-1/4	1-5/8	2
R	--	--	1/4	1/4	5/16	5/16	7/16
S	--	--	1/8	1/8	1/8	1/8	1/4
T	1/2	5/8	11/16	13/16	1	1	1-15/16
U	--	--	1/4	1/4	5/16	5/16	5/16

The NIKKISO EIKO® FLEXIFLO™ is recognized as one of the most capable and reliable pumps manufactured in the world. Our newest version offers a more user-friendly maintenance without compromising the high performance it is known for.

7 Point Advancement

- The integrated cam enclosed in the pump casing keeps the edges of the impeller free from abrasion. There is no hedge on the cam arrangement.
- The serration of the impeller bushing eases removal for daily maintenance.
- Large durometer O-ring offers easy removal for maintenance and tight seal in use.
- Three, directional ports for drainage make for easy pump installation.
- Pre-assembled shaft with deep-groove shielded ball bearings eliminate the need for a conventional spacer and does not require grease replenishment.
- Carbon versus ceramic mechanical seal as standard.
- Scrapers are attached to both front and rear bearing housing and are effective against both liquid and dust permeation.

Dimensions (inches - approximate)



