


Features:

- Design Capacities of 1.25 to 886 GPH
- Discharge Pressures to 5,075 PSIG
- Metering Accuracy of $\pm 0.5\%$
- 10:1 Turndown via Stroke Length
- Internal Hydraulic Relief Valve
- Modular Design for Ease of Upgrades
- Multiple Options for Custom Solutions
- Specifically Matched Accessories
- API 675 & HI Standards Compliant



Performance Table*												
Capacity (GPH)	Pressure (PSIG)	Speed (SPM)	Plunger Diameter	Connection Size								
1.25 2.50 3.26 4.07 5.02 6.53	5,075	32 65 85 105 130 170	10 mm	1/2"								
2.66 5.32 6.92 8.65 10.6 13.9		32 65 85 105 130 170			14 mm	1/2"						
5.31 10.6 13.8 17.3 21.2 27.6		32 65 85 105 130 170					20 mm	1" x 3/4"				
10.6 21.2 27.6 34.6 42.6 55.3		32 65 85 105 130 170							28 mm	1" x 3/4"		
21.2 42.5 55.3 69.1 85.1 111		32 65 85 105 130 170									40 mm	1.5" x 1"
42.6 85.1 110 138 170 220		32 65 85 105 130 170										
85.6 171 223 279 344 447	215	32 65 85 105 130 170	80 mm	2.5" x 2"								
				3" x 2.5"								
				170 340 442 553 681 886	100	32 65 85 105 130 170	112 mm	2.5" x 2"				
								3" x 2.5"				

The NIKKISO Milflo™ MX Series 5000 is a high performance, state-of-the-art, hydraulically actuated, diaphragm metering pump. The pump is available in simplex or multiplex configurations, with independent capacity adjustment for each pumphead.

All drive parts are fully enclosed and operate in an oil bath which minimizes friction and wear while providing protection from harsh environments. NIKKISO Milflo™ MX Series 5000 drives are all amplitude modulation design, eliminating lost motion and excess shock loads, while assuring longer pump life; and feature the new, patented technology of the X Crank for higher accuracy and efficiency.

A self-compensating hydraulic system assures automatic diaphragm position control and eliminates the need for troublesome vacuum breakers. Hydraulic valving removes any entrained air to maintain a tight hydraulic circuit and steady state accuracy.

The easy-to-read digital stroke length indication enables convenient capacity adjustment between 0.0 and 100.0% while the pump is operating or stopped. In addition to manual control, the pump can be supplied with optional automatic capacity control, making it possible for the pump to control the flow rate in proportion to various process signals. A simple, externally adjustable, internal hydraulic relief valve protects the pump and the process from pump induced overpressure situations.

*Simplex capacities shown. Multiply for multiplex pumps.

Custom Features	Accessories
Alternate Diaphragm Materials	NIKKISO HydroChek™ Calibration Columns
API 675 & HI Standards Compliant	NIKKISO HydroDamp® Pulsation Dampeners
Automatic Capacity Control	NIKKISO HydroDrive™ VSD's and Motor Controls
Sanitary Liquid End	NIKKISO HydroGarD® Back Pressure Valves
Double Diaphragm Liquid Ends	NIKKISO HydroGarD® Safety Relief Valves
Diaphragm Status Indication	NIKKISO HydroInjex™ Injection Assemblies
Liquid End Jacketing	NIKKISO HydroMix™ Agitators
Liquid Piston - Remote Liquid End	NIKKISO HydroTank® Liquid Handling Packages

Component	Materials of Construction			
Pumphead	316SS	Alloy 20	Hastelloy® C	PVC
Check Valve Body	316SS	Alloy 20	Hastelloy® C	PVC
Check Valve Seat	316SS	Alloy 20	Hastelloy® C	PVC
Check Valve Element	316SS	Alloy 20	Hastelloy® C	Ceramic
Diaphragm	PTFE	PTFE	PTFE	PTFE
O-Rings	PTFE	PTFE	PTFE	FKM

*Non-standard combinations and materials are available upon request.

